



**RADIANT
TUBING**
POLYETHYLENE-RAISED
TEMPERATURE WITH
OXY-BARRIER

STRIKING PERFORMANCE

VIPERT Radiant performs like no other tubing in the market. Based on patented technology from The Dow Chemical Company, VIPERT Radiant provides increased flexibility and relaxed memory for ease of installation.



IMPROVED FLEXIBILITY FOR EASIER INSTALLATION

With relaxed memory you'll experience less spring back than PEX for easier installation



STRENGTH & DURABILITY

Excellent hydrostatic strength at high temperatures and very high burst pressures



25-YEAR WARRANTY

CB Supplies stands behind VIPERT with a 25 year warranty



BUILT FOR EXTREME TEMPERATURES

Maintains excellent flexibility in extreme cold and hot environments



A SMALLER ENVIRONMENTAL FOOTPRINT

VIPERT is recyclable and requires less energy to be produced than PEX

Manufactured by:



With:



WWW.VIPERT.COM

(800) 665-1851
sales@cbsupplies.ca





RADIANT TUBING

POLYETHYLENE-RAISED TEMPERATURE
WITH OXY-BARRIER

APPLICATIONS

VIPERT Radiant is ideal for hydronic radiant heating, cooling and snow melting systems utilizing water or a water/glycol mix as the heat or cold transfer medium.

VIPERT RADIANT SPECS

VIPERT Radiant is available in a variety of sizes and lengths.



COILS	100' - 1200'
DIAMETERS	1/2" - 5/8" - 3/4" - 1"*
LENGTHS	20'

*More sizes to become available in the future. See price list for specific SKUs offered.

CERTIFICATIONS

VIPERT Radiant tubing has undergone all the required North American testing to ensure it is suitable for hydronic radiant heating, cooling and snow melting systems.



CAN/ULC-S101 Fire Endurance Tests of Building Construction and Materials



CAN/ULC-S102.2: Standard Method of Test for Surface Burning Characteristics of building Materials



UL263 Standard For Fire Tests of Building Construction and Materials



ASTM E84: Standard Test Method for Surface Burning Characteristics of Building Materials



NSF-rfh ASTM D2623