

TEMPERATURE (PE-RT) RESISTANCE WITH **OXY-BARRIER**



STRIKING BEREORMANCE

CB Supplies VIPERT™ Potable & Radiant PE-RT OXY barrier tubing offers industry leading performance with improved flexibility, lowest Greenhouse Gases (GHG) emission footprint and tubing is 100% recyclable, all backed by a 25-year warranty that is not compromised by your connection choices.



INDUSTRY LEADING FLEXIBILITY FOR **EASIER & FASTER INSTALLATION**

With relaxed memory you'll experience less spring back than PEX for easier and faster installations



100% RECYCLABLE

VIPERT is 100% recyclable, requires less energy to produce compared to PEX tubing, contributing to lowest GHG emissions footprint



CRIMP, EXPAND, OR PUSH

VIPERT Potable and Radiant is flexible for your preferred tubing methods, by crimping, expanding or with push style fittings, VIPERT does it all!



NO NONSENSE 25-YEAR WARRANTY

We stand behind our VIPERT with a transparent 25-year warranty regardless of fitting systems installed



STRENGTH, DURABILITY & BUILT FOR EXTREME **TEMPERATURES**

Exceeds all standards with exceptional hydrostatic strength at high temperatures and burst pressures, maintains excellent flexibility in both cold and hot environments



EASY LINE IDENTIFICATION BY COLOUR

White, red, and blue choices for Potable and VIPERT green for Radiant, available tubing sizes: 3/8" through 2"





Potable: Radiant:



1-800-665-1851

salesinfo@cbsupplies.ca











RADIANT TUBING

POLYETHYLENE OF RAISED TEMPERATURE (PE-RT) RESISTANCE WITH OXY-BARRIER

APPLICATIONS

VIPERT Radiant is ideal for hydronic radiant heating, cooling and snow melting systems utilizing water or a water/glycol mix as the heat or cold transfer medium.

VIPERT RADIANT SPECS

VIPERT Radiant is available in a variety of sizes and lengths.



COILS	100', 250', 300', 400', 500', 1000', & 1200'
DIAMETERS	3/8", 1/2", 5/8", 3/4", 1", 1-1/4", 1-1/2", & 2"
LENGTHS	20' (other sizes available by region)
COLORS	Green

CERTIFICATIONS AND LISTINGS

VIPERT Radiant tubing has undergone all the required North American testing to ensure it is suitable for hydronic radiant heating, cooling and snow melting systems.



CAN/ULC-S101 Fire Endurance Tests of Building Construction and Materials UL263 Standard For Fire Tests of Building Construction and Materials



ASTM E84: Standard Test Method for Surface Burning Characteristics of Building MaterialsCAN/ULC-S102.2: Standard Method of Test for Surface Burning Characteristics of building Materials

VIPERT.COM cbsupplies.ca

(800) 665-1851 salesinfo@cbsupplies.ca



NSF-rfh ASTM F2623



International Code Council – Evaluation Service. Plumbing, Mechanical and Fuel Gas Uniform Mechanical Code (UMC®) International Mechanical Code (IMC®)



