

MATERIAL SPECIFICATION SHEET

Imported Pressure Switches

Pressure switches are designed for the control of electrically driven water pumps, acting as an automatic on/off switch.

Product Information:

- Diaphragm actuated
- Differential increases with range
- Contacts open on increased pressure
- General purpose enclosure NEMA Type 1
- Third party certified to NSF/ANSI 372 (lead-free)
- Manufactured in an ISO 9001 facility
- 3-Year Warranty



Imported Pressure Switches

All Pressure Switches are enclosed in NEMA Type 1

CB Supplies Part #	American Granby Part #	Type	Fluid Connection	Differential PSI	Range PSI	Setting PSI	*Feature
A06221200	PS2040	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	20-40	-
A06221300	PS3050	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	30-50	-
A06221400	PS4060	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	40-60	-
A06221203	PS2040M1	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	20-40	1
A06221301	PS3050M1	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	30-50	1
A06221401	PS4060M1	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	40-60	1
A06221202	PS2040M4	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	20-40	2
A06221302	PS3050M4	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	30-50	2
A06221402	PS4060M4	Standard Adj Diff ≤ 1.5 hp	1/4" NPSF internal	15-30	20-65	40-60	2

*Features:

1. Maintained manual cut-out lever (Auto-Off)
2. Low pressure cut-off (Auto-Start-Off)